



MODEL PP70150/2,5	
Min. Applicable Size	70 mm
Max. Applicable Size	150 mm
Inflation Pressure/Working Pressure*	2,5 Bar
Max. Back Pressure**	1,0 Bar
Material	SBR+NR mixed Rubber and strong fabric
Approx. Weight	0,7 kg
Deflated Diameter	68 mm


INFLATED SHAPES

Applicable Size: Any size between DN70 up to DN150 (DN70,...., DN150)


Air filling port to inflate the plug.




DN 150 Pipe




DN125 Pipe



DN100 Pipe



DN70 Pipe



*** BACK PRESSURE CHART FOR DRY CONCRETE PIPE			
MODEL / PIPE DIAMETER	70 mm	100 mm	150 mm****
PP70150/2,5	1,7 Bar	1,4 Bar	1,0 Bar

- * : Working Pressure means Inflation pressure which is the required pressure to inflate the plug by air.
- ** : Back Pressure refers to the pressure which pushes the plug and forces it to move inside the pipeline.
- *** : The back pressures in the table are only valid for the ambient temperature at 25°C degree.
- **** : It is not recommended to use the plugs in max. diameter except dry concrete pipe, because the back pressure is related with the friction coefficient between pipe and plug. If the pipe is not concrete or the pipe surface is not clean or not dry, the friction coefficient will be smaller. So, the Plug will hold less back pressure. So, don't use the plug in limits and select the larger size plug for that kind of applications.



Drw By:Eng. IBS
Revised By:UA

Publication Date: 13/07/2015
Revision Date : 9/01/2020

Drawing Name : Model PP70150/2,5